

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**





Figure 1. (a) (b) (c). The schematic of the steps to construct a SSH Braille cell and its working configurations.




Figure 2. The working sequence of the hydraulic and latching system in Braille cell.


Initial Position




Step 1



Step 2



Microelectrodes on PVDF



+ - + - + - + - + - + -




Figure 3. An array of micro electrodes made on the PVDF polymer thin film.




Figure 4. An single row of cavities




Figure 5. An single row of cavities with bending elements working at two sides

Figure 6. An single row of cavities with membranes and supporting rod sealing at top.




Figure 7. A multi-line or full page Braille display made by adding single row of working units into an array of Braille dots.

